NOTES:


- 1. ALLOWABLE OPTICAL MATERIAL: SCHOTT: ZERODUR 542/562
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO < 3 ARCMIN
- 3. COATING (APPLY ACROSS COATING APERTURE)


\$1: ENHANCED ALUMINUM Ravg≥95% 450-650nm @ 0° AOI

S2: NONE

4. ARROW ON EDGE POINTING TOWARDS SURFACE \$1.

5. FINE GROUND SURFACE





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SHAPE	S1 PLANO	S2 PLANO	EFL (AT 587.6nm)	NA		Edmund Optics®
SURFACE ACCURACY AT 632.8nm	1/20 WAVE	NA	BFL (AT 587.6nm)	NA		
SURFACE QUALITY	60 - 40	COMMERCIAL POLISH			TITLE	1/20\(\text{Optical Flat, Zerodur, 1inch Diameter}\) ENHANCED ALUMINUM
CLEAR APERTURE	Ø 22.9	Ø 22.9				
BEVEL MAX FACE	1.0 x 45°	1.0 x 45°	ALL DIMS IN	mm	DWG NO	43412-533