NOTES:

1. SUBSTRATE MATERIAL: Fused Silica


2. SURFACE S2 TO BE PARALLEL WITH S1 TO 30 arcsec


3. COATING (APPLY ACROSS CLEAR APERTURE)

S1: UV Enhanced Aluminum R(avg) >89% @ 250 - 450nm R(avg) >85% @ 250 - 700nm S2: NONE

FINE GRIND SURFACE /4.\

5. ROHS COMPLIANT





 \mathbb{R}

FOR INFORMATION ONLY DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

-

		Edmund Optic	S®			
REV. A	S1	\$2			10mm Square LIV Enhanced Alumin	um
SURFACE QUALITY	20-10	COMMERCIAL POLISH	THIRD ANGLE	TITLE	40mm Square UV Enhanced Aluminum Coated, λ/10 Mirror	
SURFACE FLATNESS	λ/10	NA				
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG NO	68318	Sheet 1 Of 1