NOTES:

- 1. SUBSTRATE MATERIAL: FUSED SILICA
- 2. SURFACE S2 TO BE PARALLEL TO SURFACE S1 TO WITHIN 2 ACRMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE)


\$1: R(avg) ≥ 96% FROM 700 - 2000nm @ 0° AOI R(avg) ≥ 96% FROM 2000 - 10000nm @ 0° AOI

S2: NONE

4. FINE GRIND SURFACE

5. CLEAR APERTURE AND COATING APERTURE EDGES ARE OFFSET FROM THE PART EDGE BY 0.75mm

6. Rohs Compliant



FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	Edmund	Optics®
--	--------	---------

	\$1	\$2	THIRD ANGLE (#) PROJECTION		- TITLE	25.4mm, 1/10 WAVE, PROTECTED GOLD, KNIFE-EDGE PICKOFF MIRROR	
SURFACE QUALITY	20-10	FINE GRIND					
SURFACE FLATNESS	1/10 WAVE	N/A					
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	36136	SHEET 1 OF 1