NOTES:

1. SUBSTRATE: Crystalline Quartz

2. COATING (APPLY ACROSS COATING APERTURE): S1 & S2: R(AVG) <0.3%

DAMAGE THRESHOLD, PULSED: >20 J/cm², 10ns @ 10Hz @ 1064nm


3. SURFACE S1 TO BE PARALLEL TO SURFACE S2 TO WITHIN <3 ARCSEC


4. RETARDANCE: $\lambda/4 \pm \lambda/150$ @ 20°C RETARDANCE ORDER: 2nd

5. DESIGN WAVELENGTH: 355nm

6. TRANSMITTED WAVEFRONT: <λ/10 @ 632.8nm

7. ROHS: COMPLIANT





FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

GO [®] Edmun	d Optics®
------------------------------	-----------

	S1	S2	THIRD ANGLE PROJECTION		TITLE	25.4mm Dia., 355n Waye	m, λ/4 High Energy plate	
SURFACE QUALITY	20-10	20-10		1			<u>'</u>	
CLEAR APERTURE	Ø18.00	Ø18.00	ALL DIMS IN	mm	DWG NO	39164	SHEI 1 OI	DF 1