## NOTES:

- 1. SUBSTRATE: FUSED SILICA
- 2. SURFACE S2 TO BE PARALLEL TO SURFACE S1 TO WITHIN < 3 ARCMIN
- 3. COATING PERFORMANCES ACROSS CLEAR APERTURE:

T(ABS) > 99.8% @ 532nm @ 0° AOI




FINE GRIND SURFACE




SURFACES ARE EXTREMELY FRAGILE, ANY CONTACT TO OPTICAL SURFACE WILL AFFECT PERFORMANCE. DO NOT TOUCH SURFACES AND DO NOT WIPE CLEAN.



UNTREATED ANNULUS 1.25mm FROM EDGE





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2	
SHAPE	PLANO	PLANO	
SURFACE QUALITY	10-5	10-5	
CLEAR APERTURE	Ø20.32	Ø20.32	
BEVEL	PROTECTIVE AS NEEDED PROTECTIVE AS NEEDED		

		Edmund Optics®
THIRD ANGLE PROJECTION	TITLE	25.4mm Dia., 6.35mm THICK, 532nm NEBULAR™ LASER LINE WINDOW

ALL DIMS IN mm DWG NO 14649 SHEET 1 OF 1