
## NOTES:


- 1. SUBSTRATE: FLOAT GLASS
- 2. ROHS: COMPLIANT
- 3. COATING (APPLY ACROSS CLEAR APERTURE):
  - S1:

ABRASION: SEVERE, PER MIL-C-675C Paragraph 3.8.4.1 ADHESION: MIL-PRF-13830B, App B PARA. 4.4.6

R(AVG) >70% @ 400 - 700nm R(AVG) >90% @ 2000 - 10000nm

S2: NONE





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

## SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

SHAPE	S1 PLANO	S2 PLANO				<b>Edmund</b>	d Optics®
SURFACE QUALITY	80 - 50	COMMERCIAL POLISH		1		MIRROR 4-6 WAVE	RH 12 5mm DIA
CLEAR APERTURE	Ø11.25	N/A			TITLE		
SURFACE FLATNESS	4 - 6λ	N/A					
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED	ALL DIMS IN	mm	DWG NO	15487	SHEET 1 OF 1