
NOTES:


- 1. SUBSTRATE: Silicon (Si)
- 2. SURFACE S2 TO BE PARALLEL WITH S1 TO <3 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2:


R(AVG) <1% @ 1650 - 3000nm R(ABS) <2% @ 1650 - 3000nm



5. Rohs Compliant







FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

SHAPE	\$1 PLANO	S2 PLANO			8	Edm	und Optic	\$S®
CLEAR APERTURE	22.5mm	22.5mm		1		25mm DIA X 1	2.0mm THICKNESS 1.65-	3um
SURFACE QUALITY	60-40	60-40	THIRD ANGLE PROJECTION		TITLE	COATED SILICON WINDOW		
SURFACE FLATNESS	1λ	1λ		1		007112	012/00/1/1/1/12/07/	CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	17198		SHEET 1 OF 1