
NOTES:

- 1. SUBSTRATE: Silicon (Si)
- 2. SURFACE S2 TO BE PARALLEL WITH S1 TO <3 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2:


R(AVG) <1% @ 1650 - 3000nm R(ABS) <2% @ 1650 - 3000nm

4. FINE GRIND SURFACE

5. Rohs Compliant







FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2]			Edmund Optic	C®
SHAPE	PLANO	PLANO					,S
CLEAR APERTURE	45.00 mm	45.00 mm				50mm DIA. X 1.0mm THICKNESS 1.65-	3um
SURFACE QUALITY	60-40	60-40	THIRD ANGLE PROJECTION		TITLE	COATED SILICON WINDOW	
SURFACE FLATNESS	1λ	1λ				CONTED CIENCE TO THE CONTENT OF THE	QUIEET.
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	17201	SHEET 1 OF 1