
NOTES:

1. SUBSTRATE: VACUUM UV GRADE CaF2

- 2. SURFACE S2 TO BE PARALLEL WITH S1 TO < 1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) S1 & S2: R(AVG) ≤ 1.5% FROM 250-700nm @ 0° AOI R(ABS) ≤ 1.0% FROM 350-450nm @ 0° AOI

4. FINE GRIND SURFACE



FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

 -1.00 ± 0.10

-S2

/4\

S1-

SHAPE	\$1 PLANO	S2 PLANO				Edmund Optic	S [®]
SURFACE FLATNESS	2λ	2λ		TITLE	50mm Dia., 1mm Thick, UV-VIS Coated, Calcium Fluoride Window		
SURFACE QUALITY	40-20	40-20	THIRD ANGLE				
CLEAR APERTURE	Ø45.00	Ø45.00					
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN m	mm	DWG NO	22609	Sheet 1 Of 1