

[See all 19 Products in Family](#)

## 0.22 NA UV/VIS Patchcord 400 Micron Fiber w/ FC Connector



Stock #23-709 **3 In Stock**

S\$359<sup>00</sup>

**ADD TO CART**

Volume Pricing	
Qty 1-4	S\$359.80 each
Qty 5-10	S\$324.80 each
Qty 11-24	S\$288.40 each
Need More?	<a href="#">Request Quote</a>

### Product Downloads

#### General

Patchcord Type:  
Multimode Fiber Cable Type:

#### Physical & Mechanical Properties

1.5 Length (m):

400 Core Diameter (µm):

PVC MONOCOIL (0.190" OD) Jacket Material:

## Optical Properties

Nylon Coating Type:

0.22 Numerical Aperture NA:

UV-VIS Wavelength:

## Hardware & Interface Connectivity

FC/PC Connector:

## Environmental & Durability Factors

-40 to +100 Operating Temperature (°C):

## Regulatory Compliance

Compliant RoHS 2015:

View Certificate of Conformance:

Compliant Reach 250:

## Product Details

- UV/VIS and VIS/NIR Versions Available
- FC Connector Compatible with [Spatial Filters](#)
- FC Connector Compatible with [Fiber Alignment Mounts](#)
- FC and SMA Connector Options

High Quality Fiber Patchcords are designed for UV-VIS (190 - 1250nm) or VIS-NIR (300 - 2400nm) ranges. These Patchcords are 1.5 meters in length with Nylon or Tefzel coatings. With core diameters ranging from 50 – 1000µm, these patchcords provide quality solutions for a variety of core sizes. High Quality Fiber Patchcords are available with SMA905 or FC/PC connectors featuring a 0.22 numerical aperture. These Patchcords are ideal for applications requiring optimum transmission in the UV-VIS or VIS-IR wavelengths.

## Technical Information

