

[See all 14 Products in Family](#)

# LightPath 354060 | 6.33mm Dia., 0.27 NA, BBAR (350-700nm), Molded Aspheric Lens

See More by [Lightpath®](#)



Stock **#83-697** **20+ In Stock**

[Other Coating Options](#)

1  **\$\$105<sup>00</sup>**

**ADD TO CART**

Volume Pricing	
Qty 1-10	<b>\$\$105.00</b> each
Qty 11-49	<b>\$\$94.50</b> each
Need More?	<a href="#">Request Quote</a>

## Product Downloads

### General

354060 **Lightpath Lens Code:**

Aspheric Lens **Type:**

### Physical & Mechanical Properties

6.33 ±0.015 **Diameter (mm):**

5.20	Clear Aperture CA (mm):
1.57	Edge Thickness ET (mm):
2.49 ±0.05	Center Thickness CT (mm):
Protective as needed	Bevel:

## Optical Properties

9.60 @ 633nm	Effective Focal Length EFL (mm):
0.27	Numerical Aperture NA:
<a href="#">D-ZK3</a>	Substrate: <input type="checkbox"/>
±1	Focal Length Tolerance (%):
633	Aspheric Design Wavelength (nm):
BBAR (350-700nm)	Coating:
$R_{avg} \leq 0.5\%$ @ 350 - 700nm	Coating Specification:
60-40	Surface Quality:
1.85	f#:
61.16	Abbe Number ( $v_d$ ):
1.589	Index of Refraction ( $n_d$ ):
350 - 700	Wavelength Range (nm):
8.100	Working Distance (mm):
Infinite	Conjugate Distance:
633.00	Focal Length Specification Wavelength (nm):
< 0.145	Transmitted Wavefront Error ( $\lambda$ , RMS):

## Material Properties

7.6	Coefficient of Thermal Expansion CTE ( $10^{-6}/^{\circ}\text{C}$ ):
-----	--

## Regulatory Compliance

<a href="#">Compliant</a>	RoHS 2015:
<a href="#">View</a>	Certificate of Conformance:
<a href="#">Compliant</a>	Reach 247:

## Product Details

- Compact, Molded Aspheric Lens Design
- Improved Performance Compared to Doublet and Triplet Lenses
- Ideal for Laser Tools and Measurement Systems

LightPath® Laser Tool Molded Aspheric Lenses are designed to fulfill the needs of a variety of tools and measurement systems utilizing laser diodes, including leveling lasers, projectors, scanners, trackers, and gun sights. By utilizing a single aspheric lens, the need for a multi-lens system is eliminated, allowing for a more compact and robust design. Each aspheric lens is offered with various anti-reflection coatings for optimum transmission in the visible and NIR wavelength ranges. LightPath® Laser Tool Molded Aspheric Lenses' anti-reflection coating options for each lens provides <1% average reflection over the entire design wavelength range. The lenses are offered in four different diameters: 3mm, 4.70mm, 6mm, and 6.33mm.

