

[See all 76 Products in Family](#)

# LightPath 354125 | 11mm Dia., 0.50 NA, BBAR (350-700nm), Molded Aspheric Lens

See More by [Lightpath®](#)



Precision Molded Aspheric Lenses

Stock **#33-425** **20+ In Stock**

[Other Coating Options](#)

⊖ 1 ⊕ **S\$166<sup>00</sup>**

**ADD TO CART**

Volume Pricing	
Qty 1-10	<b>S\$166.60</b> each
Qty 11-49	<b>S\$149.80</b> each
Need More?	<a href="#">Request Quote</a>

Product Downloads

**General**

Thickness: 0.25 (t) (mm)  
Material: B-K7

**Compatible Window:**

354125

**Lightpath Lens Code:**

Aspheric Lens

**Type:**

Typical Applications:  
Collimate or Focus Laser Light

## Physical & Mechanical Properties

11.00 ±0.015	Diameter (mm):
10	Clear Aperture CA (mm):
1.092	Edge Thickness ET (mm):
3.64 ±0.40	Center Thickness CT (mm):
Protective as needed	Bevel:

## Optical Properties

10.00 @ 633nm	Effective Focal Length EFL (mm):
0.50	Numerical Aperture NA:
<a href="#">D-ZK3</a>	Substrate: <input type="checkbox"/>
±1	Focal Length Tolerance (%):
633	Aspheric Design Wavelength (nm):
BBAR (350-700nm)	Coating:
$R_{avg} \leq 0.5\%$ @ 350 - 700nm	Coating Specification:
60-40	Surface Quality:
1.00	f/#:
60.88	Abbe Number ( $v_d$ ):
1.586	Index of Refraction ( $n_d$ ):
350 - 700	Wavelength Range (nm):
7.8	Working Distance (mm):
Infinite	Conjugate Distance:
633.00	Focal Length Specification Wavelength (nm):
< 0.09	Transmitted Wavefront Error ( $\lambda$ , RMS):

## Material Properties

7.6	Coefficient of Thermal Expansion CTE ( $10^{-6}/^{\circ}\text{C}$ ):
-----	--

## Environmental & Durability Factors

≤200	Operating Temperature ( $^{\circ}\text{C}$ ):
------	---

## Regulatory Compliance

<a href="#">Compliant</a>	RoHS 2015:
<a href="#">View</a>	Certificate of Conformance:
<a href="#">Compliant</a>	Reach 247:

## Product Details

- Eliminate Spherical Aberration
- Multiple Coating Options Available
- Range of Numerical Apertures

LightPath® Geltech™ Molded Aspheric Lenses are used to eliminate spherical aberration and improve focusing and collimating accuracy in a variety of laser applications. Low NA aspheric lenses are designed to maintain beam shape, while high NA lenses gather all available light to maintain beam power over long distances. LightPath® Geltech™ Molded Aspheric Lenses are ideal for applications including sighting systems, bar code scanners, laser diode-to-fiber coupling, optical data storage, or biomedical lasers.

## Technical Information

