

[See all 11 Products in Family](#)

25.0/25.4mm Optic Dia., 5 Axes Optical Mount



5 Axes Optical Mount



Stock #13-776 **4 In Stock**

S\$1,057⁰⁰

ADD TO CART

Volume Pricing

| | |
|------------|-------------------------------|
| Qty 1-4 | S\$1,057.00 each |
| Qty 5-9 | S\$1,004.64 each |
| Qty 10+ | S\$898.94 each |
| Need More? | Request Quote |

Product Downloads

General

Adjustable - Linear (XYZ) & Tip-Tilt **Type:**

Circular **Type of Optics:**

Physical & Mechanical Properties

| | |
|----------------------------|--------------------------------|
| 22.0 | Clear Aperture CA (mm): |
| ±2.0 in X and Y, ±1.5 in Z | Travel (mm): |
| 0.3 | Weight (kg): |
| Black Anodized Aluminum | Construction: |
| ±2 | Tip/Tilt Angle (°): |

Threading & Mounting

| | |
|-------------|---|
| 25.0 - 25.4 | Size of Compatible Optics (mm): |
| 12.5 (Max) | Thickness of Compatible Optics (mm): |
| M6 x 1.0 | Compatible Post: |

Regulatory Compliance

| | |
|----------------------------------|------------------------------------|
| Exempt | RoHS 2015: |
| View | Certificate of Conformance: |
| Contains SVHC(s) | Reach 247: |

Product Details

- 2-Axis, 3-Axis, and 5-Axis Adjustable Mounts Available
- Options for 12.5mm (0.5"), 25mm (1"), and 50mm (2") Dia. Optics
- M6 Mounting Threads

Multi-Axis Adjustable Optic Mounts can adjust optic positioning along the X- and Y-axes, as well as through optional Z-axis and Tip/Tilt adjustment. Compact packaging allows for fine alignment adjustments without the additional use of bulkier stages. Multi-Axis Adjustable Optic Mounts are ideal for alignment adjustments in prototyping and precision laboratory benchtop optical systems. These mounts include M6 mounting threads making them compatible with our standard [Metric Stainless Steel Mounting Posts](#). A retainer ring and Delrin ring are used together to secure the optic without damaging its surface.

Technical Information

