


25mm Diameter Laser Diode Mirror



Stock **#43-532** 20+ In Stock

-

1

+

S\$44^{.80}

ADD TO CART

Volume Pricing	
Qty 1-10	S\$44.80 each
Qty 11-24	S\$35.00 each
Need More?	Request Quote

Product Downloads

General

Type:

Flat Mirror

Physical & Mechanical Properties

Diameter (mm):

25.00 ±0.25

Thickness (mm):

3.00

Dimensional Tolerance (mm):

±0.25

Optical Properties

Dielectric

Coating Type:

Dielectric Mirror (500-700nm)

Coating:

633

Design Wavelength DWL (nm):

Float Glass

Substrate:

R_{abs} >97% @633nm

Coating Specification:

80-50

Surface Quality:

Environmental & Durability Factors

ML-C-48497A

Durability:

Regulatory Compliance

Compliant

RoHS 2015:

View

Certificate of Conformance:

Compliant

Reach 247:


Product Details

- Over 95% Reflectance of Visible Laser Diode Light
- Ideal for Multiple Reflection Systems
- Coating Optimized for 633nm at 45° AOI

Visible Laser Diode Mirrors are specially coated to attain maximum reflection of visible laser diodes. Optimized for 633nm at a 45° angle of incidence, these mirrors provide 97% reflectance versus only 85 - 90% for standard first surface mirrors. This reduced loss is particularly important in multiple reflection systems, where loss can significantly impact system efficiency. Visible Laser Diode Mirrors feature a float glass substrate and are ideal for multiple reflection systems.

Technical Information

Visible Laser Diode Mirror Reflectance at 45°



@ 500nm	95.0%
@ 550nm	97.0%
@ 600nm	97.5%
@ 633nm	97.0%
@ 635nm	97.0%
@ 650nm	96.5%
@ 670nm	96.0%
@ 675nm	95.0%
@ 700nm	94.5%

Quote Your Size

Compatible Mounts