

[See all 96 Products in Family](#)

## TECHSPEC® 40mm Dia. Enhanced Aluminum Coated, N/10 ZERODUR® Mirror

See More by [SCHOTT Optical Components](#)



TECHSPEC ZERODUR N/10 First Surface Mirrors

Stock #17-779 [CONTACT US](#)

⊖ 1 ⊕ **\$278<sup>.00</sup>**

**ADD TO CART**

Volume Pricing	
Qty 1-5	<b>\$278.60</b> each
Qty 6-25	<b>\$222.60</b> each
Qty 26-49	<b>\$210.00</b> each
Need More?	<a href="#">Request Quote</a>

### Product Downloads

### General

Flat Mirror **Type:**

### Physical & Mechanical Properties

40.00 +0.00/-0.20 **Diameter (mm):**

**Back Surface:**

Commercial Polish

Protective as needed **Bevel:**

90 **Clear Aperture (%):**

Ground **Edges:**

30 **Parallelism (arcsec):**

5.00 ±0.20 **Thickness (mm):**

## Optical Properties

λ/10 **Surface Flatness (P-V):**

ZERODUR® **Substrate:** □

20-10 **Surface Quality:**

R<sub>avg</sub> >95% @450 - 650nm **Coating Specification:**

Enhanced Aluminum (450-650nm) **Coating:**

Metal **Coating Type:**

450 - 650 **Wavelength Range (nm):**

0.2 J/cm<sup>2</sup> @532nm, 10ns **Damage Threshold, Reference:** □

## Material Properties

0.1 **Coefficient of Thermal Expansion CTE (10<sup>-6</sup>/°C):**

## Regulatory Compliance

Compliant **RoHS 2015:**

View **Certificate of Conformance:**

Compliant **Reach 247:**

## Product Details

- Precision ZERODUR® Substrates
- λ/10 Flatness
- Low Coefficient of Thermal Expansion

TECHSPEC® ZERODUR® λ/10 First Surface Mirrors are well suited for applications where temperature fluctuation is a concern. The ZERODUR® substrates have a coefficient of thermal expansion (CTE) of ±0.10 x 10<sup>-6</sup>/°C, which is an order of magnitude lower than most glass types. The low CTE allows these mirrors to have a consistent reflected wavefront, even when exposed to environments with varying temperature or illumination sources with changing intensity. TECHSPEC® ZERODUR® λ/10 First Surface Mirrors feature precision polished substrates with λ/10 flatness and 20-10 surface quality. Multiple metallic and enhanced metallic coating options are available, allowing for these mirrors to be easily integrated into applications in both the visible and infrared spectrum.

**Note:** Surface flatness is measured before coating.

## Coating Curves

## Custom

Edmund Optics offers comprehensive custom manufacturing services for optical and imaging components tailored to your specific application requirements. Whether in the prototyping phase or preparing for full-scale production, we provide flexible solutions to meet your needs. Our experienced engineers are here to assist—from concept to completion.

Our capabilities include:

- Custom dimensions, materials, coatings, and more
- High-precision surface quality and flatness
- Tight tolerances and complex geometries
- Scalable production—from prototype to volume

Learn more about our [custom manufacturing capabilities](#) or submit an inquiry [here](#).