

[See all 20 Products in Family](#)

**TECHSPEC® 40mm, English Z-Stage**



TECHSPEC® Vertical Translation Stages



Stock **#66-498** **4 In Stock**

⊖ 1 ⊕ **\$\$1,015<sup>00</sup>**

**ADD TO CART**

Volume Pricing	
Qty 1-2	<b>\$\$1,015.00</b> each
Qty 3+	<b>\$\$887.60</b> each
Need More?	<a href="#">Request Quote</a>

Product Downloads

**General**

English **Type:**

**Physical & Mechanical Properties**

Linear (Z) **Type of Movement:**

**Guide System:**

40 x 40	<b>Stage Size (mm):</b>
10	<b>Travel (mm):</b>
1/4-20	<b>Center Hole:</b>
Aluminium Stage	<b>Construction:</b>
0.5	<b>Leadscrew Pitch (mm):</b>
2	<b>Load Capacity (kg):</b>
1.57 x 1.57	<b>Stage Size (inches):</b>
3	<b>Straight Line Accuracy (µm):</b>

### Hardware & Interface Connectivity

Lead Screw	<b>Type of Drive:</b>
------------	-----------------------

### Threading & Mounting

(1) 1/4-20, (4) 6-32, (8) 2-56	<b>Mounting Threads:</b>
--------------------------------	--------------------------

### Regulatory Compliance

<a href="#">Compliant</a>	<b>RoHS 2015:</b>
<a href="#">View</a>	<b>Certificate of Conformance:</b>
<a href="#">Compliant</a>	<b>REACH 241:</b>

## Product Details

[Bottom adapter plates](#), sold separately, are required to mount 30mm and 40mm stages to standard breadboards.

- Mechanically Compatible with our [TECHSPEC® Stages](#)
- Fine Micrometer Movement
- Locking Screw on Stages

Our newly developed precision TECHSPEC® Vertical Translations Stages (Z-axis stages) feature a unique and advanced crossed roller bearing guide system that provides high accuracy, rigidity and load capacity. Each stage is designed to integrate with our line of [TECHSPEC® stages](#) in order to provide flexibility in allowing the user to create a number of multi-axis configurations. These stages have a locking screw and fine micrometer movement. TECHSPEC® Vertical Translations Stages are constructed of aluminum and have a linear (Z) movement. The stages are available in both English and Metric versions and are offered in four sizes.

## Technical Information

