EO Edmund
optics | worldwide

LightPath 354260 | 543nm Alignment, 0.16 NA Fiber Collimator w/ FC/APC Connector

See More by **Lightpath®**

Fiber Optic Collimator and Focuser Assemblies

Stock **#13-555**   **20+ In Stock**

⊖ 1 ⊕   **S$488**.⁶⁰

ADD TO CART

Volume Pricing	
Qty 1-5	**S$488.60** each
Qty 6+	**S$358.40** each
Need More?	**Request Quote**

Product Downloads

General

Lightpath Lens Code:	
354260	
Type:	
Fiber Collimator	
Lens Included:	
#37-098	

Physical & Mechanical Properties

Clear Aperture CA (mm):
5.38

Bevel:
Protective as needed

Construction:
304L Stainless Steel Housing

Housing Diameter (mm):
11.00

Housing Length (mm):
20.2

Optical Properties

Effective Focal Length EFL (mm):
15.29 @ 780nm

Numerical Aperture NA:
0.16

Substrate:
D-ZK3

Coating:
BBAR (350-700nm)

Coating Specification:
R_{avg} <0.5% @ 350 - 700nm

Surface Quality:
40-20

f/#:
3.12

Wavelength Range (nm):
350 - 700

Conjugate Distance:
Infinite

Alignment Wavelength (nm):
543

Transmitted Wavefront Error (λ, RMS):
< 0.090

Hardware & Interface Connectivity

Connector:
FC/APC

Threading & Mounting

Mount:
M11 x 0.5

Regulatory Compliance

RoHS 2015:
Compliant

Certificate of Conformance:
View

Reach 247:
Compliant

Product Details

- Easy to Integrate
- Models for FC/PC, FC/APC, and SMA Connections Available
- Four Wavelength Ranges Covering 350-1600nm

LightPath® Fiber Optic Collimators are designed to collimate light exiting a fiber to a desired beam diameter or spot size or to focus light into a fiber when used in reverse. The lenses are diffraction limited, so they can achieve spot sizes down to a few microns. Lenses also feature an antireflection coating for low back reflection. LightPath® Fiber Optic Collimators are designed so that they can be used in pairs to couple the input and output light of optical devices. Optimum performance for long-term use is ensured by the factory set and tested lens alignment. Typical applications can include use with fiber coupled lasers and pigtailed receptacles, as well as communications and data transfer.

Technical Information

SMA Connector Type

Thread
MØ x 0.5

Accepts SMA Connector

Ø

L1

Length

L2

FC Connector Type

Thread
MØ x 0.5

Accepts FC Connector

Ø

L1

Length

L2

FC/APC Connectors

Thread

Accepts FC/APC Connector

-3.79°

Ø

L1

L4