


[See all 13 Products in Family](#)

5mm Dia., 0.4mm Thick, SCHOTT D263® T eco Window

See More by [SCHOTT Optical Components](#)



SCHOTT D263® T eco Windows

Stock #29-358 **12 In Stock**

S\$28⁰⁰

ADD TO CART

Volume Pricing	
Qty 1-5	S\$28.00 each
Qty 6-25	S\$22.40 each
Qty 26-49	S\$21.00 each
Need More?	Request Quote

Product Downloads

General

Protective Window Type:

Glass Type of Window:

Physical & Mechanical Properties

Clear Aperture CA (mm):

4.50	Diameter (mm):
5.00 ±0.25	
	Thickness (mm):
0.40 ±0.05	
	Bevel:
Protective as needed	
	Clear Aperture (%):
90	
	Edges:
Cut	
	Poisson's Ratio:
0.21	
	Young's Modulus (GPa):
72.9	

Optical Properties

	Coating:
Uncoated	
	Substrate: <input type="checkbox"/>
D263® T eco	
	Index of Refraction (n_d):
1.523	
	Surface Quality:
80-50	
	Wavelength Range (nm):
350 - 2000	

Material Properties

	Density (g/cm³):
2.51	
	Transformation Temperature (°C):
557	
	Coefficient of Thermal Expansion CTE (10⁻⁶/°C):
7.2 (+20 to +300°C)	

Regulatory Compliance

Compliant	RoHS 2015:
View	Certificate of Conformance:
Compliant	Reach 247:

Need different specs or modifications?

Edmund Optics offers comprehensive custom manufacturing services for optical and imaging components tailored to your specific application requirements. Whether in the prototyping phase or preparing for full-scale production, we provide flexible solutions to meet your needs. Our experienced engineers are here to assist—from concept to completion.

Our capabilities include:

- Custom dimensions, materials, coatings, and more
- High-precision surface quality and flatness
- Tight tolerances and complex geometries
- Scalable production—from prototype to volume

Learn more about our [custom manufacturing capabilities](#) or submit an inquiry [here](#).

Product Details

- Thin 0.4mm SCHOTT D263® T eco Substrates
- Excellent Glass Alternative to Plastic Optics
- Ideal for Weight and Space Sensitive Applications

SCHOTT D263® T eco Windows feature thin 0.4mm thick, eco-friendly manufactured glass substrates with high transmission in the visible and near-infrared (NIR) spectra. These windows are manufactured through a precision down-draw manufacturing process, achieving surface roughness <1nm RMS with excellent thickness tolerances and low total thickness variation (TTV). SCHOTT D263® T eco glass has high chemical resistance and environmental durability and is an excellent alternative to plastic in automotive and electronics applications requiring lightweight optics. SCHOTT D263® T eco Windows are ideal for use as cover glass for resistive touch panels, substrates for capacitive touch sensors, or as substrates for optical filters used in mobile devices or LiDAR units.

Technical Information

SCHOTT D263® T eco Typical Transmission



Quote Your Size
