

[See all 11 Products in Family](#)

6.11" High Bright LED Diffuselite, White, Strobed

See More by [Advanced Illumination](#)



Advanced Illumination Diffuselite LED Illuminators

Stock **#83-269** [CONTACT US](#)

-

1

+

S\$2,324^{.00}

ADD TO CART

Volume Pricing	
Qty 1+	S\$2,324.00 each
Need More?	Request Quote

Note: This item requires accessories for use | [Learn More](#)

Product Downloads

General	
DL097-WHII3	Model Number:
50,000	LED Lifetime (hours):
12.00	Number of LEDs:
2.00	Number of Channels:

LED Illuminator	Type of Illumination:
Advanced Illumination	Note:
	Optional Manual Intensity Adjustment #86-887 and #89-555 are Available
Diffuse	Manufacturer:
	Geometry:
Strobed	Illumination Mode:

Physical & Mechanical Properties

161.00	Height (mm):
227.00	Outer Diameter (mm):

160.00	Field Coverage (mm):
--------	----------------------

Optical Properties

White	Color:
13 - 75	Working Distance (mm):

N/A	Wavelength Tolerance (nm):
-----	----------------------------

±10 Edge to Edge (Dependent on Working Distance)	Light Distribution (%):
--	-------------------------

Electrical

30.00	Maximum Trigger Frequency (Hz):
-------	---------------------------------

30 - 300	Strobe Duration (µs):
----------	-----------------------

Hardware & Interface Connectivity

Flying Leads	Connector:
Power Supply Required and Sold Separately. USA: #66-855 Europe: #66-855 Japan: #89-513 Korea: #33-773 China: #66-855	Power Supply:

Environmental & Durability Factors

0 to 65	Operating Temperature (°C):
---------	-----------------------------

Regulatory Compliance

Compliant	RoHS 2015:
View	Certificate of Conformance:
Contains SVHC(s)	Reach 233:

Product Details

- Ideal for Illuminating Curved Surfaces
- Well Suited for Inspecting Small, Specular Objects
- Variable Intensity and Strobed Options

Advanced Illumination Diffuselite LED Illuminators are ideal for inspecting small, reflective objects. LED intensity can be varied through the in-line potentiometer, and the projected light distribution edge to edge is ±10%. The 3.35" and 6.35" models feature high-brightness LEDs. The strobed models' flash duration is dependent on a trigger signal or potentiometer setting. The duration of the strobe can be adjusted from 30 - 300µs via a knob located in the back of the unit. The trigger input signal of the Advanced Illumination Diffuselite LED Illuminator is CMOS/TTL compatible. The maximum trigger frequency is 30 Hz.

Note: Required 24V power supply [#66-855](#). [Accessories for Advanced Illumination products](#) are available and sold separately.