

[See all 146 Products in Family](#)

Allied Vision Alvium 1800 U-2050c, 1" 20.2MP, USB 3.0 Color Camera (Board Level)

See More by [Allied Vision](#)



Allied Vision Alvium Camera, Board Level (Front)



Stock **#14-902** [CONTACT US](#)

⊖ 1 ⊕ **\$\$854⁰⁰**

ADD TO CART

Volume Pricing

Qty 1+	\$\$854.00 each
Need More?	Request Quote

Product Downloads

Color **Spectrum:**

General

Color Camera **Type:**

1800 U-2050c **Model Number:**

Manufacturer:

Allied Vision

Camera Series:

Alvium

Physical & Mechanical Properties

Dimensions (mm):

13 x26 x26 (includes connectors)

Weight (g):

15

Housing:

Board Level

Sensor

Image Buffer:

256KB

Sensor Format:

1"

Resolution (Megapixels):

20.20

Frame Rate (fps):

17.00

Pixels (H x V):

5,496 x3,672

Pixel Size, H x V (µm):

2.4 x2.4

Sensing Area, H x V (mm):

13.1 x8.8

Imaging Sensor:

Sony IMX183

Type of Sensor:

Progressive Scan CMOS

Shutter Type:

Rolling

Pixel Depth:

8/10 bit

Exposure Time:

17µs - 10s

Machine Vision Standard:

USB3 Vision v1.0, GenICam

Electrical

Power Consumption (W):

3.2

Hardware & Interface Connectivity

Interface:

USB 3.0 Gen 1

Connector:

USB 3.0 Gen 1, Micro-B

Power Supply:

Power over USB or via GPIO

GPIOs:

4 Programmable TTL GPIOs

Synchronization:

Hardware Trigger (GPIO) or Software Trigger

Interface Port Orientation:

Back Panel

GPIO Connector Type:

7-pin JST

Threading & Mounting

Mount:

No Lens Mount

Mounting Threads:

No Mounting Threads/Tripod Adapter

Environmental & Durability Factors

Operating Temperature (°C):

-20 to +85 (mainboard temperature)

Storage Temperature (°C):

-20 to +85

Regulatory Compliance

RoHS 2015:

Compliant

Product Details

- Compact, Low Cost, High Performance Design for Machine Vision and Embedded Applications
- ALVUM® System on Chip (SoC) Technology with Onboard Imaging Preprocessing
- Up to 24.60 MegaPixels, 1.2" Sensor Format
- [Allied Vision Alvium Right Angle USB 3.1 Cameras](#) Also Available

Allied Vision Alvium USB 3.0 Cameras feature a lightweight compact form factor with ALVUM® System on Chip (SoC) technology, offering a comprehensive image processing library for advanced onboard image correction and preprocessing functions to relieve host computer and processor workload. In addition to smart camera operations, the unique SoC design also allows for low power consumption and ease of integration, making them ideal for next generation machine vision, robotics and embedded vision applications. The cameras feature a variety of popular Sony Pregius and On Semi CMOS sensors with high image quality, fast frame rate and USB3 Vision interface standard. The actively aligned lens mount minimizes inconsistency and variation. Allied Vision Alvium USB 3.0 Cameras feature a USB port on the back panel and are available in a variety of monochrome, color, and NIR configurations, including C-Mount, CS-Mount, and S-Mount. Full housing versions are best suited for prototyping, development and end user uses. Partial housing and board level configurations have exposed image sensor PCB without heat sinks to reduce space and facilitate system integration making them ideal for OEM embedded design.

Note: Board level versions do not have a lens mount.