

[See all 7 Products in Family](#)

# Coherent® High-Sensitivity Thermopile Sensor PS10 1098350 | 1W Max Power

See More by [Coherent®](#)



Coherent® High-Sensitivity Thermopile Sensors

Stock **#12-416** **2 In Stock**

S\$2,499<sup>00</sup>

**ADD TO CART**

Volume Pricing	
Qty 1+	S\$2,499.00 each
Need More?	<a href="#">Request Quote</a>

Product Downloads

**General**

**Model Number:**  
PS10 Coherent Part Number: 1098350

**Type:**  
[Meter required](#)

**Linearity (%):**  
±1

**Calibration Uncertainty (%):**  
1

**Cooling Method:**

Air

Response Time (s):

2

Note:

Includes a Removable Light Tube to Minimize Background Radiation Effects

Compatible Meters:

[#35-203](#), [#12-393](#), [#59-978](#),  
[#88-411](#), [#66-277](#), [#88-412](#)

Maximum Incident Energy Density:

50mJ/cm<sup>2</sup> (10ns, 1064nm)

## Physical & Mechanical Properties

Active Area Diameter (mm):

10

## Optical Properties

Calibration Wavelength (nm):

514

Wavelength Range (nm):

300 - 11000

Wavelength Range (µm):

0.3 - 11

## Sensor

Type of Sensor:

Thermopile

## Electrical

Maximum Incident Power Density (kW/cm<sup>2</sup>):

0.5

Power Range:

100µW - 1W

Maximum Power (W):

1

Power Resolution:

10µW

## Hardware & Interface Connectivity

Length of Cable (m):

2

Computer Interface:

DB-25

## Environmental & Durability Factors

Thermally Stabilized:

Yes

## Regulatory Compliance

RoHS 2015:

[Exempt](#)

Reach 224:

[Contains SVHC\(s\)](#)

Certificate of Conformance:

[View](#)

## Product Details

- Broad Spectral Range with High Sensitivity and High Resolution
- Large Active Area Sensors up to 19mm in Diameter
- Flat Broadband Output with No Saturation above 1mW/cm<sup>2</sup>

Coherent® High-Sensitivity Thermopile Sensors are designed to have a broad spectral response to accommodate an array of lasers with different wavelengths. The large active area and high resolution of these thermopile sensors allows for accurate measurements of low-power lasers. A range of models are available to meet specific needs relating to thermal stability, background radiation, and air current effect. Coherent® High-Sensitivity Thermopile Sensors are designed to accurately measure the laser power of small laser diodes, HeNe lasers, and small ion lasers. Unique to this design, these sensors will not saturate when laser power exceeds 1mW/cm<sup>2</sup>.