

[See all 14 Products in Family](#)

Coherent® OBIS™ LX SF 1448284 | 405nm LX SF 40mW Single Frequency Laser

See More by [Coherent®](#)



Stock #18-722 **1 In Stock**

⊖ 1 ⊕ \$9,730⁰⁰

ADD TO CART

Volume Pricing	
Qty 1+	\$9,730.00 each
Need More?	Request Quote

Product Downloads



General

<5	Warm-Up Time (minutes):
Coherent®	Manufacturer:
Diode	Type of Laser:
IIIb	Laser Class - CDRH:
1448284	Model Number:

Physical & Mechanical Properties

Pointing Stability ($\mu\text{rad}/^\circ\text{C}$):

<5

Pointing Stability (μrad):

<30

Optical Properties

Polarization:

100:1 (minimum)

Spatial Mode:

TEM_{00}

Wavelength (nm):

405.00 \pm 1

Mode Quality, M^2 :

\leq 1.5

Beam Diameter Tolerance (mm):

\pm 0.1

Beam Diameter (mm):

0.4

Spectral Line Width (MHz):

160

Beam Divergence (mrad):

Full-Angle: <2

Color:

Violet

Spectral Line Width (pm):

0.3 (maximum)

Electrical

Output Power (mW):

40

Power Stability (%):

<1

RMS Noise:

\leq 0.05% (20Hz to 20MHz)

Peak-to-Peak Noise:

<0.5% (20Hz to 20kHz)

Hardware & Interface Connectivity

Power Supply:

Power Supply Required and Sold Separately.

USA: [#87-473](#)

Europe: [#87-473](#)

Japan: [#87-473](#)

Korea: [#87-473](#)

China: [#87-473](#)

Output Type:

Free Space

Environmental & Durability Factors

Operating Temperature ($^\circ\text{C}$):

+10 to +50

Regulatory Compliance

RoHS 2015:

[Exempt](#)

Reach 224:

[Contains SVHC\(s\)](#)

Certificate of Conformance:

[View](#)

Product Details

- Single Frequency, Collimated, TEM_{00} Output Beam
- Excellent Signal-to-Noise Ratio
- Compatible With All OBIS LX/LS Power Supplies, Software, and Accessories

Coherent® Single Frequency OBIS™ LX Laser Systems incorporate Coherent's SureLock™ volume holographic grating (VHG) stabilized laser diodes to deliver consistent, single frequency performance in the same form factor as all other [OBIS LX/LS platforms](#). Available in 405, 633, and 660nm, these laser systems excel in application spaces requiring very low RMS signal-to-noise of less than 0.05%. An excellent alternative to stabilized HeNe lasers, each laser is stabilized using Coherent's PowerLocker® volume holographic grating ensuring precise and stable center wavelengths, low temperature dependence, and consistent optical performance. Coherent® Single Frequency OBIS™ LX Laser Systems are ideal for applications such as confocal microscopy, DNA sequencing, flow cytometry, and interferometry and are compatible with all other OBIS LX/LS power supplies, accessories, and software.

OBIS Laser System Startup Guide

This downloadable PDF provides guidance on interfacing with OBIS controllers and power supplies, mounting and connecting the heatsink, and starting modulation.

[Download Startup Guide](#)

