

OBIS XT Single Laser Remote with Power Cable

See More by [Coherent®](#)



Stock **#75-329** NEW **2 In Stock**

-

1

+

S\$870⁰⁰

ADD TO CART

Volume Pricing	
Qty 1+	S\$870.00 each
Need More?	Request Quote

Note: This item requires accessories for use | [Learn More](#)

Product Downloads

SPECIFICATIONS

General

<2

Warm-Up Time (minutes):

Digital Modulation Impedance (Ω):

SMB Connector, 0 V to 3 V, 50 Ω input impedance

Electrical	
2	Power Consumption (W):
Analog Modulation Impedance (Ω): SMB Connector, 0V to 5V, 50 Ω or 2000 Ω input impedance	
Hardware & Interface Connectivity	
USB 2.0, Mini B and RS-232	Computer Interface:
Environmental & Durability Factors	
+0 to +40	Operating Temperature (°C):
Regulatory Compliance	
View	Certificate of Conformance:

PRODUCT DETAILS

- Compact, Thermally Efficient Design for Ease of Life Science System Integration
- 320, 349, and 640nm Wavelength Options Available
- Integrated Controller with RS-232, RS-485, and USB Interfaces

Coherent OBIS XT Laser Systems offer an advanced extension of the [OBIS LS/LX](#), delivering powerful performance across ultraviolet and visible wavelengths. These lasers are available in UV wavelengths of 320 and 349nm, with output power options ranging from 20 to 150mW, and a higher-power 640nm wavelength option with output powers of 400 or 500mW. Flexible communication interfaces, including RS-232, RS-485, and USB, allow for seamless integration and real-time control in complex applications. Coherent OBIS XT Laser Systems are designed to simplify system integration, utilizing their compact form factor, integrated controller, as well as a low thermal output. This reduces the need for external cooling and streamlines OEM and end-user implementation. OBIS XT lasers are ideal for a wide range of applications, including life sciences, biomedical, flow cytometry, DNA Sequencing, and fluorescence microscopy.