

[See all 17 Products in Family](#)

SI Free-Space Balanced Photoreceiver, 320-1000nm



#90-639 SI Free-Space Balanced Photoreceiver, 320-1000nm

Stock **#90-639** NEW **2 In Stock**

⊖ 1 ⊕ **\$4,900⁰⁰**

ADD TO CART

Volume Pricing

Qty 1+	\$4,900.00 each
Need More?	Request Quote

Product Downloads

General

Note:

- Includes:
 (2) Threaded coupler ring
 Lemo®3-pin connector
 (3) Adapter SMA (male) to BNC (female)
 Datasheet

Physical & Mechanical Properties

Weight (g):
410

Dimensions (mm):
Case Size: 80 x 80 x 30.5

Optical Properties

Spectral Range:

320 - 1000 nm

Sensor

Detector Type:

Si-PIN photodiode

Electrical

Transimpedance Gain (Ω):

2×10^4 or 6×10^4 (switchable)

Noise Equivalent Power NEP ($W/Hz^{1/2}$):

7.4×10^{-12} @880nm

Bandwidth (-3 db):

100 MHz

Output Signal:

± 1.0 V at 50 Ω load (for linear gain and low harmonic distortion), maximum ± 2.0 V at 50 Ω load

Conversion Gain (V/W):

10.8×10^3 or 32.4×10^3 (@850 nm switchable)

Common Mode Rejection (dB):

50

Hardware & Interface Connectivity

Power Requirement:

± 15 V (± 14.5 V ... ± 16.5 V) -90 / +120 mA

Power Supply:

Power Supply Required and Sold Separately.

USA: [#59-180](#)

Europe: [#59-180](#)

Japan: Not Available

Korea: Not Available

China: [#59-180](#)

Environmental & Durability Factors

Operating Temperature ($^{\circ}C$):

0 to +60

Regulatory Compliance

RoHS 2015:

[Compliant](#)

Certificate of Conformance:

[View](#)

Product Details

- Subtracts Two Photodiode Signals for Differential Detection
- Improved Signal to Noise Ratio (SNR) for Weak or Modulated Optical Signals
- High Common-Mode Noise Suppression for Improved Measurement Sensitivity and Accuracy
- Available in Si and InGaAs models for UV-VIS and NIR spectral ranges

Balanced Photoreceivers use true differential detection by subtracting the photocurrents from two matched photodiodes, producing a single electrical output proportional to the difference in optical power between the two inputs. This suppresses common-mode noise, such as laser intensity fluctuations, improving SNR and measurement sensitivity. Balanced Photoreceivers are engineered with a low-noise transimpedance amplifier, which ensures stable, consistent performance for precision optical measurements. Available in Si and InGaAs models for UV-VIS (320-1000nm) and NIR (800-1700nm) spectral ranges, these photoreceivers are ideal for coherent optical detection, interferometry, spectroscopy, and optical coherence tomography (OCT).

Note: Power supply sold separately. Please see specifications for more details.